

Battery Type Lift Table CADDIE

- Battery meter with three-color demarcation.
- Easy-to-use table design
- Equipped with a battery charger that allows charging at any time (from AC200~240V power supply).

- Moving the table upward and downward with ease at the flip of a switch.
- Provided with a safety-sensitive Lowering adjustment valve.
- Incorporates an automatic load check valve.



LT-D550-9L



LT-D800-10



● LIFT / LOWER pushbutton switch



● Three-color battery meter




● Battery charger (Built in type)

Self-propelled Lift Table CADDIE


- Moving the table upward and downward with ease at the flip of a switch.
- Provided with a handheld U-type drive that ensures smooth traveling performance.
- Provided with a safety-sensitive Lowering adjustment valve.
- Incorporates an automatic load check valve.

- Battery meter with three-color demarcation.
- Equipped with a battery charger that allows charging at any time (from AC200~240V power supply).
- Powerful electric braking.

- Dimensions (Battery type)



- Dimensions (Self-propelled Battery type)



LT-U550-9L



LT-U800-10

Specifications of Battery Type Lift Table CADDIE

Specifications	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size Length×Width (mm)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)	Steering Wheel Dia.φ×Width (mm)	Load Wheel Dia.φ×Width (mm)	Battery	Lifting Time (Seconds)	Net Weight (Kg)
Model												
LT-D550-9L	550	330	950	900×600	1,150	600	900	Rubber 150×42	Rubber 150×42	DC12V	6-10	120
LT-D800-10	800	340	1,040	1,000×600	1,250	600	900	Urethane 150×42	Urethane 150×42	48AH/5HR	9-18	150

※Includes built-in automatic battery charger (AC200 - 240V).

Specifications of Self-propelled Lift Table CADDIE

Specifications	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size Length×Width (mm)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)	Traveling speed (Km / h)		Steering Wheel Dia.φ×Width (mm)	Load Wheel Dia.φ×Width (mm)	Drive Wheel Dia.φ×Width (mm)	Battery	Breaking	Lifting Time (Seconds)	Net Weight (Kg)
								With No Load	With Load							
Model																
LT-U550-9L	550	330	950	900×600	1,410	820	1,190	0-2.4	0-2.2	Rubber 150×42	Rubber 150×42	Urethane	DC12V	Electric	6-10	148
LT-U800-10	800	340	1,040	1,000×600	1,510	830	1,190	0-2.4	0-2.2	Urethane 150×42	Urethane 150×42	160×36	48AH/5HR	Breaking	9-18	178

※Includes built-in automatic battery charger (AC200 - 240V).

LT-S Type

AC100V, same as household power source
Originally developed power cylinder for steady up and down
Automatic control of downward speed depend on the load weight (with in the capacity range)
Microcomputer on-boarded
Quick dropping protection function
Bellow-type cover equipped model for safety and dust prevention



Specifications of Lift Table COTEE (LT-S type)

Specifications	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size		Power Source	Lifting Time (Seconds)	Operation	Net Weight (Kg)
				Width	Length				
Model				A	B				
LT-S10-0407	100	80	580	400	720	AC 100V	10	Foot Switch	36
LT-S10-0509				520	850				
LT-2S10-0407				400	650				
LT-2S10-0509	200	1,050	520	850		23		50	
LT-S25-0407	250	150	650	400	720		22		45
LT-S25-0509				520	850		22	50	
LT-S10-0509B	100	80	580	520	850		10		47
LT-2S10-0509B				200	1,050		23	59	
LT-S25-0509B	250	150	650	520	850		22		60

Attention: The power supply must be over AC 100V/5A
When the max. weight loaded, using times must be set as within 1 time / min.
※ This lift table is designed as uniformly distributed load. Load equally on the more than 80% of the table surface.
※ B type means Bellow-type cover equipped products. LT-2S type means double scissors.

LT-F Type

Max. Capacity; 3,000kg is available for low profile type
Foot switch is standard (Pushbutton available as option)
Pressure adjustable hydraulic unit keeps the lowering speed constant, even though the loading weight is changed



Specifications of Lift Table COTEE (LT-F type)

Specifications	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size		Power Source	Lifting Time (60/50Hz) (Seconds)	Operation	Hydraulic Unit	Net Weight (Kg)	
				Width	Length						
Model				A	B						
LT-F200-0712	180	1,000	1,200	36	44	AC 200V	36/44	Foot Switch	Built-in	250	
LT-F200-0716	2,000	205	1,120	700	1,620						46/56
LT-F200-1020	215	1,465	1,000	2,000	39/46						
LT-F300-0716	220	1,135	700	1,620	64/77		64/77		450		
LT-F300-1020	3,000	270	1,520	1,000	2,000		59/70		690		

※Using times must be set as within 150 times / 8hours.
※This lift table is designed as uniformly distributed load.

LT-E Type

Wide variety of models for various purposes and uses
Originally developed hydraulic lifting mechanism for smooth up and down
Mounted type easily combined with assembly and process lines
Pushbutton switch for easy operation, Foot switch available as option



Specifications of Lift Table COTEE (LT-E type)

Specifications	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size		Power Source	Lifting Time (60/50Hz) (Seconds)	Operation	Hydraulic Unit	Net Weight (Kg)
				Width	Length					
Model				A	B					
LT-E20-0507	200	130	530	500	650	AC 100V	17/21	Push	Built-in	63
LT-E25-0508	250	150	715	810	810		28/34			82
LT-2E30-0510	300	235	1,405	520	1,010	AC 100V	24/29	Push	Separate	140
LT-2E30-0510A							137			
LT-E50-0510	500	150	800	460	650	AC 200V	16/20	Botton Switch	Built-in	121
LT-2E50-0507							18/22			83 (23)
LT-E75-0510	750	150	800	520	1,010	AC 200V	23/23	Push	Built-in	122
LT-E100-0609							8/10			161
LT-E100-0610	1,000	155	555	850	1,000	AC 200V	11/13	Push	Built-in	175
LT-E100-0613							20/24			225
LT-E100-0809	1,000	155	555	850	1,000	AC 200V	8/10	Push	Built-in	180
LT-E100-0810							11/13			194
LT-E100-0813	1,000	155	555	850	1,000	AC 200V	11/13	Push	Built-in	244
LT-E100-1013							20/24			259
LT-E100-1020	205	1,510	1,000	2,000	21/25		21/25		357	

Specifications of Lift Table COTEE (LT-E type, Ultra Low Profile)

Specifications	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size		Power Source	Lifting Time (60/50Hz) (Seconds)	Operation	Hydraulic Unit	Net Weight (Kg)
				Width	Length					
Model				A	B					
LT-E25L-0508	250	59	529	810	810	AC 200V	9/11	Push	Separate	93 (23)
LT-E25L-0510	759	1,010	13/16	111 (23)						
LT-E50L-0508	500	60	760	520	1,010	AC 200V	17/21	Push	Separate	99 (23)
LT-E50L-0510							26/31			118 (23)
LT-E100L-0513	1,000	76	976	1,280	1,280	AC 200V	21/25	Push	Separate	194 (32)
LT-E100L-0813							215 (32)			

※This lift table is designed as uniformly distributed load. Load equally on the more than 80% of the table surface.
※Net weight in () are weights of hydraulic units.
※LT-2E type means double scissors.

As of October 2014

Created by Highly Experienced Hydraulic Equipment Makers.

Originality Produces Know-how

O.P.K. OKUDAYA GIKEN CO., LTD.

285 Tanjo, Mihara-ku, Sakai-city, Osaka 587-0011, JAPAN.
TEL 81-723-61-7861 FAX 81-723-62-2102
E-mail: trading@opk.co.jp

URL : <http://www.opk.co.jp>



REGISTERED ORGANIZATION
NO.0989-ISO9001
NO.0993-ISO14001
Acquired by head office



JAB
OS Accreditation
R002, R1002

* Products with special specifications besides those with standard specifications are manufactured as well. Feel free to contact OKUDAYA GIKEN.
The specifications described in this catalog are subject to change without notice for product improvement.
* The colors of actual products may be more or less different from those printed in this catalog.

All rights reserved.

LT

LIFT TABLE CADDIE/COTEE



— Japan Quality —



FOUNDED 1934



OKUDAYA GIKEN CO., LTD.

OSAKA JAPAN

ESTABLISHED 1954

Manual Type Lift Table CADDIE

Ensures stable and infallible transfer.
Versatile work support with simple design.

- Equipped with a quick-lifting mechanism as a standard accessory that will double the lifting speed when the pedal is turned to the left (except the LT-H150 and LT-H250-8S).
- Incorporates an automatic load check valve.
- Ensures ease of use with a tight turning circle.
- Provided with speed control valve as a standard accessory that prevents the table from quickly moving downward (provided as an option to the LT-H150).
- Simple design that matches work environments.
- Powerful parking brake.



With No Quick-lifting Mechanism



LT-H100-6: Provided with speed control valve
 LT-H150-7S: Provided with speed control valve
 LT-H150-7: Provided with folding handle
 LT-H250-8S: Provided with speed control valve

With Quick-lifting Mechanism and Speed Control Valve



LT-H250-8: Provided with speed control valve
 LT-H550-9L: Provided with speed control valve
 LT-H800-10: Provided with speed control valve



LT-WH200-13: Double scissor type provided with speed control valve
 LT-WH300-15-A: Double scissor type provided with speed control valve
 LT-WH500-10: Double scissor type provided with speed control valve

Stainless Type Lift Table CADDIE



LT-H150-7SU: Stainless steel type provided with speed control valve
 LT-H250-8SU: Stainless steel type provided with speed control valve
 LT-H550-9SU: Stainless steel type provided with speed control valve

Quick-lifting Magic Pedal
 Doubling the table lifting speed.
 ※Except the LT-H150 and LT-H250-8S.


Speed control Valve (Safety Lowering Mechanism)
 Prevents the table from quickly moving downward.
 ※Provided as an option to the LT-H150.

Options (for All Models)

- Bellows-type Cover**

 Ensures improved safety at work and dust prevention.
- Handless-type Table**

 Long objects can be loaded onto the handless-type table. The lowest position of the table is in a range between approximately 35 and 100 mm, which is higher than a normally available range. *The position varies with each model.



Specifications of Manual Lift Table CADDIE

Specification	Capacity (Kg)	Min. H (mm)		Max. H (mm)	Table Size Length×Width (mm)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)	Steering Wheel Dia.φ×Width (mm)	Load Wheel Dia.φ×Width (mm)	Pump Pedaling (Number of Times)	Net Weight (Kg)
		A	B									
LT-H100-6	100	600	600	600	550×350	830	355	750	Rubber 100×25	Rubber 100×25	9	20
LT-H150-7S	150	210	740	700×400	950	400	840	815	Rubber 100×32	Rubber 100×32	13	30
LT-H150-7											24	32
LT-H250-8S	250	245	850	800×500	1,050	500	845	880	Rubber 130×38	Rubber 130×38	24	47
LT-H250-8											24 (12)	67
LT-H400-8M	400	310	900×600	1,150	600	880	880	880	Rubber 150×42	Rubber 150×42	36 (18)	67
LT-H400-8L											48 (27)	70
LT-WH500-10	500	380	1,000	650×500	900	500	900	900	Rubber 150×42	Rubber 150×42	51 (30)	83
LT-H550-8M	550	310	830	800×500	1,050	500	845	900	Urethane 150×42	Urethane 150×42	57 (29)	75
LT-H550-9L											62 (36)	117
LT-H800-10	800	340	1,070	1,000×600	1,250	600	900	900	Urethane 150×42	Urethane 150×42	62 (36)	117

Specifications of Manual Lift Table CADDIE (Double Scissor Type)

Specification	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size Length×Width (mm)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)	Steering Wheel Dia.φ×Width (mm)	Load Wheel Dia.φ×Width (mm)	Pump Pedaling (Number of Times)	Net Weight (Kg)
LT-WH200-13	200	450	1,300	800×500	1,050	500	880	Rubber 130×38	Rubber 130×38	59 (31)	91
LT-WH300-15-A	300	410	1,500	900×600	1,150	600	900	Rubber 150×42	Rubber 150×42	63 (38)	116

Specifications of Manual Lift Table CADDIE (Stainless Steel Type)

Specification	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size Length×Width (mm)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)	Steering Wheel Dia.φ×Width (mm)	Load Wheel Dia.φ×Width (mm)	Pump Pedaling (Number of Times)	Net Weight (Kg)
LT-H150-7SU	150	210	740	700×400	950	400	860	Urethane 100×25	Urethane 100×25	20 (10)	36
LT-H250-8SU	250	245	850	800×500	1,050	500	845	Urethane 100×32	Urethane 100×32	24 (12)	56
LT-H550-9SU	500	330	980	900×600	1,150	600	900	Urethane 150×42	Urethane 150×42	51 (30)	98

*Lifting times in () are quick-lifting times on the condition that no loads are imposed.

Low Profile Type Lift Table CADDIE



LT-H200L-6: Low profile type provided with speed control valve

Specifications of Manual Lift Table CADDIE (Low Profile Type)

Specifications	Capacity (Kg)	Min. H (mm)	Max. H (mm)	Table Size Length×Width (mm)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)	Steering Wheel Dia.φ×Width (mm)	Load Wheel Dia.φ×Width (mm)	Pump Pedaling (Number of Times)	Net Weight (Kg)
LT-H200L-6	200	85	600	800×500	1,200	500	860	Rubber 100×32	Urethane	28 (13)	64
LT-H400L-6	400	87	600	900×600	1,330	600	890	Rubber 130×38	75×38	61 (34)	94

*Lifting times in () are quick-lifting times on the condition that no loads are imposed.

Leveler Type Lift Table CADDIE

Maintain the same Load Height

- By adjusting the spring's tension, maintain the same the load height.
- Workers can keep better body position, so it prevents backaches.
- It can be used as a work table or load stocking trolley
- One of the casters has a brake
- It's useful for production lines and parts supplements.



LT-B200-7: Adjust the spring tension and set the load weight
 LT-B400-7L: Maintenance Stopper



Specifications of Leveler CADDIE

Specifications	Adjustable Capacity (Kg)	Table Height (mm)	Table Size Length×Width (mm)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)	Steering Wheel Dia.φ×Width (mm)	Load Wheel Dia.φ×Width (mm)	Net Weight (Kg)
LT-B200-7	100-200	370-770	800×500	940	500	910	Rubber 100×32	Rubber 100×32	54
LT-B400-7M	250-400	380-770	800×500	945	600	910	Urethane 100×32	Urethane 100×32	81
LT-B400-7L			900×600	1,045					84

